



Finer Machines... Finest Constructions

Skimfloater G900 E / G700 E

The Skimfloater is a highly efficient, hand held, light weight machine for floating and trowelling concrete surfaces.

- Two/Single speed operation for electric version.
- Dead man's Grip for operator safety.
- Adjustable & foldable handle .
- Dual function - floating and trowelling
- Easy changeover from disc to blades
- Blade angle adjustable while machine is in operation.
- All controls on handle, easily accessible.
- G 700E also ideally suitable for Epoxy Screed finishing.



TECHNICAL DATA

	G900 E	G700 E
Electric Motor	3 Phase, 415 V, 50 Hz.	3 Phase, 415 V, 50 Hz.
Power	1.8 / 1.5 kW.	1.8 / 1.5 kW.
Rated Current	5.0 / 3.3 A.	5.0 / 3.3 A.
Speed (Output)	115 / 57 rpm.	115 / 57 rpm.
Max. reach	3 mtrs.	2.2 mtrs.
Outer diameter of guard	1000 mm.	780 mm.
Diameter of floating disc	985 mm.	750 mm.
Working dia.	900 mm.	700 mm.
No. of Trowelling Blades	4	4
Machine weight with 4 blades	78 kg	72 Kg
Weight of floating disc	16 kg	9 kg



Safety Device



Floating Disc



Trowelling Blades